

LED Classico Downlight



SPEC SHEET



Applications

Interior retail, display, residential, commercial applications where lamp quality, reliability and performance is essential, in particular locations such as public spaces, reception areas, hotels and health sector.

Features & Benefits

- Plastic coated aluminium profile for good heat dissipation.
- Thermal conductive plastic housing make sure safe light.
- V-0 flame rating.
- Triac dimmable version for option.
- Working Temperature: -20°C ~ 40°C.
- Driver built-in.
- Warranty: 3 years.

Specifications

Code	CLS-CDL-7W	CLS-CDL-12W	CLS-CDL-17W
Watts	7 W	12 W	17 W
Current	90mA	90mA	130mA
Input Voltage	110~220 VAC 50/60Hz		
Power Factor	>0.9		
Color Temperature	3000K / 4000K / 6000K		
Lumens	520 lm (3000K) 550 lm (4000K) 550 lm (6000K)	1000 lm (3000K) 1050 lm (4000K) 1050 lm (6000K)	1430 lm (3000K) 1500 lm (4000K) 1500 lm (6000K)
Efficiency (lm/w)	74 (3000K) 78 (4000K) 78 (6000K)	84 (3000K) 88 (4000K) 88 (6000K)	84 (3000K) 88 (4000K) 88 (6000K)
CRI	Ra≥80		
Beam Angle	90°		
Dimension	ø92 x 63.5 mm	ø145 x 75 mm	ø174 x 78.5 mm
Dimension	ø68 - 80 mm	ø120 - 130 mm	ø145 - 155 mm
IP Rating	IP 44		
Rated Life	40,000 hrs		

