

Splinter Gen-2

Specification

- Plastic coated aluminium profile for good heat dissipation.
- Thermal conductive plastic housing.
- V-0 flame rating.
- Triac dimmable version for option.
- Working Temperature: -20°C ~ 40°C.
- Driver built-in.

Product Codes





Code	Version	Dim (mm)	Cutout (mm)
SPLINTERG2-5W	Splinter Gen-2 5W, CCT 3000K / 4000K / 6000K, Lumens 400lm / 425lm / 425lm, CRI ≥80, PF ≥0.9, IP20, 50,000hrs	Ø95x57.5	Ø68-80
SPLINTERG2-7W	Splinter Gen-2 7W, CCT 3000K / 4000K / 6000K, Lumens 560lm / 590lm / 590lm, CRI ≥80, PF ≥0.9, IP20, 50,000hrs	Ø95x57.5	Ø68-80
SPLINTERG2-10W	Splinter Gen-2 10W, CCT 3000K / 4000K / 6000K, Lumens 860lm / 900lm / 900lm, CRI ≥80, PF ≥0.9, IP20, 50,000hrs	Ø113x59	Ø90-102
SPLINTERG2-14W	Splinter Gen-2 14W, CCT 3000K / 4000K / 6000K, Lumens 1200lm / 1260lm / 1260lm, CRI ≥80, PF ≥0.9, IP20, 50,000hrs	Ø145x65.8	Ø120-130
SPLINTERG2-17W	Splinter Gen-2 17W, CCT 3000K / 4000K / 6000K, Lumens 1450lm / 1530lm / 1530lm, CRI ≥80, PF ≥0.9, IP20, 50,000hrs	Ø174x68.5	Ø145-155
SPLINTERG2-20W	Splinter Gen-2 20W, CCT 3000K / 4000K / 6000K, Lumens 1780lm / 1880lm / 1880lm, CRI ≥80, PF ≥0.9, IP20, 50,000hrs	Ø244x84.5	Ø195-120
SPLINTERG2-25W	Splinter Gen-2 25W, CCT 3000K / 4000K / 6000K, Lumens 2330lm / 2450lm / 2450lm, CRI ≥80, PF ≥0.9, IP20, 50,000hrs	Ø244x84.5	Ø195-120



Design Application

Residential, Apartments, Lobbies, Foyers, Retail, Restaurants, Bars and clubs where an energy efficient and reliable lamp life is esseal.

Performance



Max Dim (mm)
600 or 1200

PDF Prepared: 09.09.2016 17:09pm, Last page update: Sep 2016



PIERLITE
professional lighting solutions