



Classico Downlight

Features & Benefits

- Plastic coated aluminum profile for good heat dissipation.
- Thermal conductive plastic housing make sure safe light.
- V-0 flame rating.
- Triac dimmable version for option.
- Working Temperature: -20°C ~ 40°C.
- Built-in driver.
- Warranty: 2 years.

Classico Downlight



Applications

Interior retail, display, residential, commercial applications where lamp quality, reliability and performance is essential, in particular locations such as public spaces, reception areas, hotels and health sectors.

LED Classico Highly efficient, high performance LED downlight range with an overall height of less than 80mm, making it an ideal choice for low ceiling void applications. Classico series caters to all lighting demands of general lighting applications.

Specifications

CODE	WATTS	Voltage	CRI	CCT	Lumens	Beam	Power Factor	IP Rating	DIM (mm)	Cutout (mm)				
CLS-CDL-7W-3K	7W	110-240V	Ra>80	3000K	590 lm	90°	>0.9	IP44	Ø90x63.5	Ø68-80				
CLS-CDL-7W-4K				4000K	590 lm									
CLS-CDL-7W-6K				6000K	640 lm									
CLS-CDL-12W-3K	12W			Ra>80	3000K				1000 lm	90°	>0.9	IP44	Ø145x75	Ø120-130
CLS-CDL-12W-4K					4000K				1050 lm					
CLS-CDL-12W-6K					6000K				1050 lm					
CLS-CDL-17W-3K	17W			Ra>80	3000K				1500 lm	90°	>0.9	IP44	Ø174x78.5	Ø145-155
CLS-CDL-17W-4K					4000K				1600 lm					
CLS-CDL-17W-6K					6000K				1600 lm					

