



Thunder Highbay

Features & Benefits

- High performance Nichia757G design
- Efficacy up to 110 - 130lm/W
- Energy savings up to 90%, (depending on installation and usage patterns)
- Superior uniformity
- Superior temperature stability
- Temperature tested at toughest conditions
- Sosen / Meanwell driver
- Operating range -40°C~+50°C
- Body: Aluminium alloy + PC
- Stainless steel screws
- Pure Aluminum heatsink
- IP44 / IP65 protection rating

Thunder Highbay



Thunder Highbay is a classic industrial fixture that combines modern lighting technologies and a high level design. This fixture provides not only the perfect solution to various industrial applications, but also integrates its elegant style with different space environments, demonstrating the real art of lighting.

Specifications

CODE	WATTS	Voltage	Beam Angle	PF (≥)	CRI (Ra≥)	CCT	Lumens	Chip / Driver	Dimension	IP Rating	Lifespan @ 50° C ambient temp.	Weight
CLS-TH60W	60 W	90-295VAC					6600 lm	Nichia / Meanwell	Φ200x144	IP44		1.9 kg
CLS-TH100W	100 W		120°	>0.95	Ra>80	3000K/ 4000K/ 5000K/ 5700K	13000 lm		Φ200x210		40000 hrs	2.8 kg
CLS-TH150W	150 W	90-305VAC				3000K/ 4000K/ 5000K/ 5700K/ 6500K	19500 lm	Nichia / Sosen	Φ260x208	IP65		4.5 kg

